



POLI-FLEX® FLAME RETARDANT

Product Information

POLI-FLEX® FLAME RETARDANT is an ecologically proven polyurethane film with matt, reflection free surface.

POLI-FLEX® FLAME RETARDANT is a flame-retardant textile transfer film according to DIN EN ISO 4589-2.

POLI-FLEX® FLAME RETARDANT is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic. and can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

POLI-FLEX® FLAME RETARDANT can be cut with all current plotters. We recommend using a standard 45° knife. After weeding the cut flex film is transferred by heat press. The PET liner should be removed warm. Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX® NYLON.

The soft, elastic transfer film offers a comfortable textile touch and convinces due to high wearing comfort. POLI-FLEX® FLAME RETARDANT excels due to an excellent opacity and the self-adhesive PET liner enables a reposition. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals.

Guarantee for a secure and long-lasting bond of POLI-FLEX® FLAME RETARDANT is only given when following the specified temperature and pressure conditions.

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Standard Dimensions

60" x 30yd
30" x 30yd
20" x 30yd
15" x 30yd

Technical Data

Transfer Film:	Polyurethane, cast
Adhesive:	Polyurethane-hotmelt
Thickness [mm]:	0,095 +/- 10 %
Liner:	PET-film, self-adhesive

Transfer Conditions

Temperature:	320° F
Pressure:	medium pressure
Time:	15 sec.

Wash Resistance

Wash resistance:	60 °C Only color or mild detergent. Wash textile inside out. Suitable for tumble drying.
------------------	---

POLI-TAPE USA Inc.
8100-2 Westside Industrial DR
Jacksonville, FL 32219 - USA

Phone: +1 904 215 14 11
Toll Free: +1 888 690 05 41

E-Mail: info@politape.us
Internet: www.politape.us

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.